

Model	Lumen package	Color temperature [K]		
	LED17S	830/840	1,0	
	LED27S	830/840	1,0	
ST440T	LED39S	830/840	1,0	
ST440S	LED19S	FMT	1,0	IPT label
11105	LED19S	ROSE	1,0	
	LED27S	ROSE	1,0	
	LED27S	CH	1,0	
	LED27S	FR	1,0	

650 °C

10 °C

240V

The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced!





^{2/4}











	ST4 LED		ST4 LED RO	19S	ST4 LED1 FM	9S		440 027S, , FR	ST4 LED RC		ST4 LED	-	Inrush current
DRIVER	PSU	PSD VLC	PSU	PSD VLC	PSU	PSD VLC	PSU	PSD VLC	PSU	PSD VLC	PSU	PSD VLC	
Inom(A)	0,07 0,1		0,12		0,1		0,14	0,14					
lmax(A)	18	20,4	18	20,4	18	20,4	6,1	20,4	18	20,4	11	20,4	
Tref(us) (@ Imax 50%)	250	195	250	195	250	195	310	195	250	195	306	195	max/2
MCB		Max. products											
B-16A	34	24	34	24	34	24	34	24	34	24	34	24	Time



© 2018 Signify Holding All rights reserved. This document contains information relating to the product portfolio of Signify which information may be subject to change. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.. All other trademarks are owned by Signify Holding or their respective owners.

Signify Holding. The Netherlands

PHILIPS